

Manufacturer's Specifications

WAC II Weathered Acrylic Cleaner II

1. PRODUCT NAME

WAC II is a high strength weathered acrylic roof cleaner designed specifically for cleaning weathered Conklin acrylic roof coatings, Hy-Crown® and aged Ethylene Propylene Diene Monomer (EPDM) roof membranes.

2. MANUFACTURER

Conklin Company Inc.
551 Valley Park Drive
P.O. Box 155
Shakopee, Minnesota 55379
(952) 445-6010

3. PRODUCT DESCRIPTION

BASIC USE: WAC II is a unique, highly effective cleaner designed specifically for cleaning Conklin weathered acrylic roof coatings and membranes. In addition, WAC II is used for cleaning aged EPDM roofs prior to the application of the Conklin EPDM coating system.

LIMITATIONS: When using WAC II, it is important to thoroughly remove ALL dirt, grease, chalk and debris and any remaining WAC II residue prior to applying coatings. Best results are obtained by wetting the roof surface with water prior to cleaning. The use of a stiff bristle broom may be needed to scrub extremely dirty areas such as low spots.

COMPOSITION AND MATERIALS:

SIZES: WAC II is available in 5-gallon containers.

COVERAGE RATES: Coverage rates will vary depending on roof condition. WAC II should yield approximately 400 – 500 square feet per gallon.

4. APPLICATION

WAC II should be applied at full strength with a brush, roller, and conventional airless or portable tank sprayer. The cleaner is designed to be applied at full strength – DO NOT DILUTE. Once applied, allow the cleaner to remain on the roof surface for a minimum of 20 minutes prior to water rinse, i.e., with high-pressure spray. Make sure to remove all residues and let roof surface dry thoroughly.

The specifications, properties and performance materials described on this spec sheet are based on information believed to be reliable. They are subject to change and improvement as research continues. All surfaces should be thoroughly investigated and tested and the performance of WAC II deemed satisfactory before application.

5. STORAGE

Keep product from freezing.

6. DISPOSAL

Dispose of product in accordance with local, state and federal regulations.

7. SAFETY

DANGER: CORROSIVE. VAPOR HARMFUL. WILL CAUSE BURNS TO EYES AND SKIN. HARMFUL OR FATAL IF SWALLOWED - CONTACT PHYSICIAN IMMEDIATELY. Keep out of the reach of children. Avoid contact with plants, shrubs and grass. Use only in well-ventilated areas, and close container after each use.

First Aid: Eyes - immediately flush with plenty of water for at least 15 minutes, and seek immediate medical attention. Skin – wash thoroughly with large amounts of soap and water, and seek a physician if irritation persists. ingestion – if swallowed, **DO NOT INDUCE VOMITING**, dilute with two to three glasses of water or milk, and immediately contact a poison control center or physician for further instructions. Inhalation – immediately move victim to fresh air, and give oxygen, if needed. Seek medical attention if respiratory irritation persists.

Contains: Sodium Silicate Liquid (CAS #1344-09-8) and Sodium Tripolyphosphate (CAS #77758-29-4)

Proposition 65 Statement: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

For U.S. Health Hazard Information, call (800) 228-5635
HMIS: 3-0-0-X

8. GUARANTEE

This product falls within Conklin's general product guarantee.

**Conklin Company Inc.
Building Products Division**

Specialty Coatings
Paints
Caulks
Waterproofing Systems

Independent Business Owner: